

500 ml Round Tub

Product No: PC501

Available Lids PL501



BASIC DATA

Volume Brimful	600 ml
Filling Volume	500 ml
Weight	15 g
Tamper Evidence	No

Tolerances

Dimensions	± %5
Volume/Weight	± %3

DIMENSIONS

External Diameter Top	116,20 mm	Height	80 mm
External Diameter Bottom	95,60 mm		

DECORATION

Decoration Available	IML	Label Type	Wrap-around Label
----------------------	-----	------------	-------------------

MATERIAL



MASTERBATCH COLOURS

Colours according to selected pantone colours

LOGISTIC INFORMATION

	Container	Lid
Pieces per Pallet	10.560	21.120
Pallet Height	2380 mm	1700 mm
Pallet Weight	201 kg	190 kg
Pallet Sizes	L: 1200 mm	W:800 mm

PERFORMANCES

Hot Filling Up to 80-90 °C

Hot Temperatures The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot temperatures and care must be taken in relation to stacking immediately after hot filling

Cold Temperatures Freezing conditions require special resins available on request.

Shelf Life The compliance of the product to the technical specifications in this datasheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.

500 ml Round Lid

Product No: PL501



BASIC DATA

Tolerances

Weight 8 g

Dimensions ± %5
Volume/Weight ± %3

DIMENSIONS

External Diameter 120,70 mm Height 9 mm

DECORATION

Decoration Available IML Label Type Cross Label

MATERIAL

MASTERBATCH COLOURS



Colours according to selected pantone colours

LOGISTIC INFORMATION

	Container	Lid
Pieces per Pallet	10.560	21.120
Pallet Height	2380 mm	1700 mm
Pallet Weight	201 kg	190 kg
Pallet Sizes	L: 1200 mm	W:800 mm

PERFORMANCES

Hot Filling Up to 80-90 °C

Hot Temperatures The material chosen has a very good heat resistance and the packaging is suitable for hot filling. Notably, plastic packaging become flexible when subjected to hot temperatures and care must be taken in relation to stacking immediately after hot filling

Cold Temperatures Freezing conditions require special resins available on request.

Shelf Life The compliance of the product to the technical specifications in this datasheet is guaranteed for 12 months after the date of the delivery subject to suitable storage. Suitable storage include protection of e.g. direct sun light, rain, very low temperatures or very high temperatures over a long period.